According to the Australian Work Health and Safety Regulations

Initial preparation date: 06.04.2020 Page 1 of 12

Silicone Sealant - Oxime - Grey

SECTION 1: Identification

Product identifier

Product name: Silicone Sealant - Oxime - Grey **Product code:** 32327AUS, 32927, 32507AUS

Recommended use of the product and restriction on use

Relevant identified uses: Not determined or not applicable. **Uses advised against:** Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer: **Supplier: United States Australia** J-B Weld Company, LLC HPP Lunds 400 CMH Road

1/195 Jackson Rd

Sulphur Springs, TX 75482Sunnybank Hills, Qld 4109

903-885-7696 1300-306-781

Emergency telephone number:

Australia

InfoTrac 1300-366-961 (24 hours)

SECTION 2: Hazard(s) identification

GHS classification:

Skin irritation, category 2 Serious eye damage, category 1 Skin sensitization, category 1 Carcinogenicity, category 1B

Label elements

Hazard pictograms:







Signal word: Danger

Hazard statements:

H315 Causes skin irritation

H318 Causes serious eye damage

H317 May cause an allergic skin reaction

H350 May cause cancer

Precautionary statements:

P264 Wash hands thoroughly after handling

P280 Wear face protection

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray

According to the Australian Work Health and Safety Regulations

Initial preparation date: 06.04.2020 Page 2 of 12

Silicone Sealant - Oxime - Grey

P272 Contaminated work clothing should not be allowed out of the workplace

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P321 Specific treatment (see supplemental first aid instruction on this label)

P362 Take off contaminated clothing and wash before reuse

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 Immediately call a POISON CENTER or doctor/physician

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P308+P313 IF exposed or concerned: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container in accordance with local regulations

Hazards not otherwise classified:

None

SECTION 3: Composition and information on ingredients

Identification	Name	Weight %
CAS number: 64742-46-7	Distillates (petroleum), hydrotreated middle	<10
CAS number: 17689-77-9	Triacetoxyethylsilane	<5
CAS number: 919-30-2	3-aminopropyltriethoxysilane	<1.5
CAS number: 22984-54-9	Butan-2-one O,O',O''-(methylsilylidyne)trioxime	<5
CAS number: 96-29-7	Methyl ethyl ketoxime	<5
CAS number: 2224-33-1	Butan-2-one O,O',O''-(vinylsilylidyne)trioxime	<5
CAS number: 7631-86-9	Silicon dioxide (amorphous)	<10
CAS number: 1317-65-3	Limestone	10-30
CAS number: 13463-67-7	Titanium Dioxide	<5
CAS number: 1333-86-4	Bounded Carbon Black	<1

Additional Information:

Carbon black is classified as a carcinogen only in its respirable form. Since the carbon black in this product is not respirable, it does not contribute to the product's carcinogenicity in the form presented.

Although this product contains Titanium Dioxide, the Titanium Dioxide is bound and the particles are not of

According to the Australian Work Health and Safety Regulations

Initial preparation date: 06.04.2020 Page 3 of 12

Silicone Sealant - Oxime - Grey

respirable size.

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After eye contact:

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Exposure may cause cancer.

Immediate medical attention and special treatment

Specific treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Fire fighting measures

Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable extinguishing media:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 06.04.2020 Page 4 of 12

Silicone Sealant - Oxime - Grey

Do not use water jet.

Specific hazards during fire-fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist. vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage precautions

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Do not get in eyes. Avoid contact with skin and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 06.04.2020 Page 5 of 12

Silicone Sealant - Oxime - Grey

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Australia	Distillates (petroleum), hydrotreated middle	64742-46-7	TWA: 5 mg/m³ (Oil mist, refined mineral)
	Silicon dioxide (amorphous)	7631-86-9	TWA: 10 mg/m³ (Silica amorphous, precipitated silica, & silica gel)
	Silicon dioxide (amorphous)	7631-86-9	TWA: 2 mg/m³ (Fumed silica, respirable dust)
	Limestone	1317-65-3	8-Hour TWA: 10 mg/m ³
	Titanium Dioxide	13463-67-7	TWA: 10 mg/m³ (National Workplace OELs)
	Bounded Carbon Black	1333-86-4	8-Hour TWA: 3 mg/m³ (Workplace Exposure Standards for Airborne Contaminants)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

Page 6 of 12

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Grey paste
Odor	Not determined or not available.
Odor threshold	Not determined or not available.
рН	10.1
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	100 °C (212 °F)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	1.427 g/cm³
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible materials:

None known.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

According to the Australian Work Health and Safety Regulations

Initial preparation date: 06.04.2020 Page 7 of 12

Silicone Sealant - Oxime - Grey

SECTION 11: Hazard information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Distillates (petroleum), hydrotreated middle	oral	LD50 Rat: 5000 mg/kg
	inhalation	LC50 Rat: 4.6 mg/L
3-aminopropyltriethoxysilane	oral	LD50 rat: 1780 mg/kg
	inhalation	LC50 Rat: >5 ppmV (6 hours)
	dermal	LD50 Rabbit: >4000 mg/kg
Butan-2-one O,O',O''-	oral	LD50 Rat: 2453 mg/kg
(methylsilylidyne)trioxime	dermal	LD50 Rat: >2000 mg/kg
Methyl ethyl ketoxime	oral	LD50 Rat: 2326 mg/kg
	dermal	LD50 Rabbit: 1000 mg/kg
Silicon dioxide (amorphous)	oral	LD50 Rat: > 5000 mg/kg
	dermal	LD50 Rat: > 5000 mg/kg
	inhalation	LC50 Rat: > 58.8 mg/L (4hr)
Titanium Dioxide	oral	LD50 Mouse: > 5000 mg/kg
	inhalation	LC50 Rat: 5.09 mg/L (4 hr)
Bounded Carbon Black	oral	LD50 Rat: >15400 mg/kg
	dermal	LD50 Rabbit: >3000 mg/kg

Skin corrosion/irritation

Assessment:

Causes skin irritation.

Product data:

No data available.

Substance data:

Name	Result
3-aminopropyltriethoxysilane	Causes severe skin burns.
Butan-2-one O,O',O''- (methylsilylidyne)trioxime	Causes skin irritation.

Serious eye damage/irritation

Assessment:

Causes serious eye damage.

Product data:

No data available.

Substance data:

Name	Result
3-aminopropyltriethoxysilane	Causes serious eye damage.
Butan-2-one O,O',O''- (methylsilylidyne)trioxime	Causes serious eye irritation.

Generated using Total SDS $\sp{\scriptscriptstyle\mathsf{TM}}$ (patent-pending), www.GSMSDS.com

According to the Australian Work Health and Safety Regulations

Initial preparation date: 06.04.2020 Page 8 of 12

Silicone Sealant - Oxime - Grey

Name	Result
Methyl ethyl ketoxime	Causes serious eye damage.

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction.

Product data:No data available.

Substance data:

Name	Result
Butan-2-one O,O',O''- (methylsilylidyne)trioxime	May cause an allergic skin reaction.
Methyl ethyl ketoxime	May cause an allergic skin reaction.

Carcinogenicity

Assessment:

May cause cancer.

Product data: No data available.

Substance data:

Name	Species	Result
Distillates (petroleum), hydrotreated middle		May cause cancer.
Titanium Dioxide		Airborne, unbound particles of respirable size are known to cause cancer.
Bounded Carbon Black		The carcinogenic classification only applies to airborne, unbound particles of respirable size.

International Agency for Research on Cancer (IARC):

Name	Classification
Silicon dioxide (amorphous)	Group 3
Titanium Dioxide	Group 2B
Bounded Carbon Black	Group 2B

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

According to the Australian Work Health and Safety Regulations

Initial preparation date: 06.04.2020 Page 9 of 12

Silicone Sealant - Oxime - Grey

Product data:No data available.

Substance data: No data available.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Information on likely routes of exposure:

Ocular, dermal, inhalation, ingestion.

Symptoms related to the physical, chemical and toxicological characteristics:

Refer to Section 4 of this SDS.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result	
3-aminopropyltriethoxysilane	LC50 Brachydanio rerio: >934 mg/L (96 hours)	
	EC50 Daphnia magna: 331 mg/L (48 hours)	
Butan-2-one O,O',O''-	LC50 Pimephales promelas: 972 mg/L (96 hours)	
(methylsilylidyne)trioxime	EC50 Daphnia magna: 231.84 mg/L (48 hours)	
Methyl ethyl ketoxime	LC50 Oryzias latipes: 100 mg/L (96h)	

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
	NOEC Oryzias latipes: 57.67 mg/L (14 days)
(methylsilylidyne)trioxime	NOEC Daphnia magna: >115.34 mg/L (21 days)
Methyl ethyl ketoxime	NOEC Oryzias latipes: 50 mg/L (14 d)

Persistence and degradability

Product data: No data available.

Substance data:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 06.04.2020 Page 10 of 12

Silicone Sealant - Oxime - Grey

Name	Result
Butan-2-one O,O',O''- (methylsilylidyne)trioxime	Not readily biodegradable.
Methyl ethyl ketoxime	Inherent degradability in water and soil.
Titanium Dioxide	Degradation/biodegradation testing is not relevant for metals and metal compounds that are not (bio)degradable, including titanium dioxide.
Bounded Carbon Black	The substance will not be biodegraded.

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
3-aminopropyltriethoxysilane	BCF: 3.4
Butan-2-one 0,0',0''- (methylsilylidyne)trioxime	BCF: <3; Low potential for bioaccumulation.
Methyl ethyl ketoxime	BCF: 5.8
Silicon dioxide (amorphous)	BCF: 3.16 L/kg
Bounded Carbon Black	Bioaccumulation is not expected to occur.

Mobility in soil

Product data: No data available.

Substance data:

Name	Result
3-aminopropyltriethoxysilane	Low potential for adsorption.
Butan-2-one O,O',O''- (methylsilylidyne)trioxime	Koc at 20 °C: 302700
Silicon dioxide (amorphous)	Mobile (log Koc: 1.337)

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT. **vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

Substance data:

PBT assessment:

Distillates (petroleum), hydrotreated middle	This substance is a UVCB and does not contain constituents included in the SVHC candidate list as PBT at concentrations above 0.1%.
3-aminopropyltriethoxysilane	The substance is not PBT.
Butan-2-one O,O',O''- (methylsilylidyne)trioxime	Substance is not PBT.
Methyl ethyl ketoxime	The substance is not PBT.
Silicon dioxide (amorphous)	This substance is not PBT.
Titanium Dioxide	According to Annex XIII of regulation (EC) 1907/2006 a PBT assessment shall not be conducted for inorganic substances. Titanium dioxide is an inorganic substance, thus a PBT assessment is not required.
Bounded Carbon Black	The substance is not PBT.

vPvB assessment:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 06.04.2020 Page 11 of 12

Silicone Sealant - Oxime - Grey

Distillates (petroleum), hydrotreated middle	This substance is a UVCB and does not contain constituents included in the SVHC candidate list as vPvB at concentrations above 0.1%.
3-aminopropyltriethoxysilane	The substance is not vPvB.
Butan-2-one O,O',O''- (methylsilylidyne)trioxime	Substance is not vPvB.
Methyl ethyl ketoxime	The substance is not vPvB.
Silicon dioxide (amorphous)	This substance is not vPvB.
Titanium Dioxide	According to Annex XIII of regulation (EC) 1907/2006 a vPvB assessment shall not be conducted for inorganic substances. Titanium dioxide is an inorganic substance, thus a vPvB assessment is not required.
Bounded Carbon Black	The substance is not vPvB.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport information

Australian Dangerous Goods (ADG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None

According to the Australian Work Health and Safety Regulations

Initial preparation date: 06.04.2020 Page 12 of 12

Silicone Sealant - Oxime - Grey

Packing group	None
Environmental hazards	None
Special precautions for user	None

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
Bulk Name	None
Ship type	None
Pollution category	None

SECTION 15: Regulatory information

Australia regulations

Australian Inventory of Chemical Substances (AICS): All ingredients are listed or exempt. Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):

Ingredient Name	CAS	Schedules
Methyl ethyl ketoxime	96-29-7	6

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 06.04.2020

Revision Notes:

Revision Date	Notes
2020-06-04	Classification change; composition change.

Additional information:

Version 2

End of Safety Data Sheet